FWG

FIFTH WHEEL GREASE

WITH

GRAPHITE

The **FWG-1, 2** and **L** are GRAPHITE based FIFTH WHEEL GREASES specifically designed to meet the demands of truckers. The **FWG-1, 2** and **L** are formulated by using a premium quality thickening agent, carefully selected base oils and GRAPHITE as well as tackifiers, extreme-pressure, anti-wear and anti-corrosion additives.

The **FWG-1, 2** and **L** greases stand out with the following properties :

- Excellent adhesion
- Superior water washout resistance
- Superior extreme-pressure and anti-wear performance
- Outstanding load carrying capacity
- Superior rust and corrosion resistance

TECHNICAL DATA :

	FWG-1	FWG-2	FWG-L
▪ N.L.G.I. grade :	1	2	2
▪ Color :	black	black	black
▪ Thickener :	lithium	lithium	lithium
▪ Graphite, % :	2	2	2
▪ Dropping point, °C (°F) :	185 (325)	185 (325)	185 (325)
▪ Base oil ;			
- Viscosity @ 40°C, SUS :	425	425	425
- Viscosity @ 100°C, SUS :	60	60	60
▪ Consistency, worked penetration :			
- 60 strokes, mm/10 :	315	285	285
▪ Timken OK load, lbs (kg) :	55 (25)	55 (25)	55 (25)

Sizes	Product numbers		Sizes	Product numbers
Grease	FWG-1	FWG-2	Liquid	FWG-L
312 g	N. D.	136312	1 L	134001
400 g	N. D.	136400	4 L	134004
17 kg	135017	136017	20 L	134020
55 kg	135055	136055	55 L	134055

The data provided in this document is for information purposes only. **HIPERTECH INC.**, having no control over the application and the use of this product, limits its responsibility to the quality of the product supplied.

2200, Léon-Harmel, suite 6, Québec (Québec) Canada G1N 4L2
Phone : **(418) 687-5533** Fax : (418) 687-5534
E-mail : hipertech@hipertech.com